

CREMONINI VIRGILIO SRL
METAL SHELVES

ISSUED ON: MARCH 5, 2024

SHOULDERS CAPACITY CHART " SERIE 2000" SHELVING

CROSS BEAM	nr.	2	3	4	5	6	7	8	9
------------	-----	---	---	---	---	---	---	---	---

SIDE H. 200 CM.	KG.	1.340	1.440	1.540	1.620	//	//	//	//
SIDE H. 250 CM.	KG.	1.270	1.360	1.450	1.540	1.620	//	//	//
SIDE H. 300 CM.	KG.	1.220	1.300	1.380	1.460	1.540	1.620	//	//
SIDE H. 350 CM.	KG.	//	1.240	1.320	1.400	1.480	1.560	1.620	//
SIDE H. 400 CM.	KG.	//	1.200	1.270	1.340	1.410	1.480	1.550	//
SIDE H. 450 CM.	KG.	//	//	1.220	1.290	1.360	1.420	1.480	1540
SIDE H. 500 CM.	KG	//	//	1170	1220	1270	1320	1370	1420
SIDE H. 550 CM.	KG	//	//	//	1170	1220	1270	1320	1370
SIDE H. 600 CM.	KG	//	//	//	1120	1170	1220	1270	1320

NOTE:

- 1) The declared capacities are intended with the first shelf anchored to the 3rd upright slot starting from below.
- 2) The shelving must be strictly fixed to the wall. When this is not possible, anchor with top tie rods. Contact the technical office for the correct configuration or for any particular condition of use.
- 3) The load must be evenly distributed from bottom to top and the shelves must be mounted as equidistant from each other as possible.
 Consult the shelf capacity table to avoid exceeding the total load on the shelves of a single span, related to the capacity of the corresponding uprights.
 Please contact the technical office for the correct configuration.